KVD Data Review - A Work in Progress

A Word On Estimated Uranium Ore Radiometric Grades



José Eduardo Torres Petroleum Engineer Chemical Engineer EPA, Region 6 Dallas, Texas A WORD (OR TWO) ON ESTIMATED URANIUM RADIOMETRIC ORE GRADES IN THE GARCIA HILL AREA, KLEBERG COUNTY, TX:

In the past, Kleberg County citizens have inquired with EPA about the amount of uranium ore in the Goliad Aquifer in the Garcia Hill area, following the high uranium concentrations observed in the Garcia Hill community's ground water supply (see Figure 1).


More specifically, in recent days, Ms. Elizabeth Cumberland asked whether EPA had been able to establish how the ore grade in the area compares to the cut-off grade value of 0.13% U3O8 that operator Strathmore established for its Roca Honda mining site (see Table I). Ms. Cumberland provided the Agency with numerous area well logs in the wake of a complaint filed by Mr. Teo Saenz, which prompted the GW/UIC Section to take a close look at the GR readings in those logs.

This work is an effort by the Section to satisfy the citizens' inquiries and, in particular, Ms. Cumberland's question on uranium ore grade, all part of the efforts towards addressing Mr. Saenz's complaint. The map in Figure 2 highlights the wells (see arrows) that were selected for analysis based primarily on their location relative to the Garcia Hill community, and to the impacted W-24 and W-25 wells.

Table II lists the highest ore grade values, as %U3O8, that were estimated for given points in the formation in the selected 11 area wells, while Figure 3 compares those "point ore grade values" to the "cut-off values" selected by operators Strathmore and URI: 0.13% and 0.11%, respectively. The available Uranium concentrations for the area's Goliad water shown in Table II, and in Figures 4 and 5, are generally near or below the EPA standard of 30 μ g/L for dissolved Uranium. These baseline Uranium concentrations show that the water in an aquifer with naturally occurring very low grade Uranium ore can be suitable for human consumption, as long as it remains undisturbed.

The Uranium concentration shown in Table III for the City of Kingsville PWS EP004 well compares reasonably well with the above concentrations, suggesting that ore grades in the city may generally be in the range of those illustrated in Table II. Figure 6 compares the stratigraphic columns for Garcia Hill wells and one City of Kingsville PWS well, and is submitted as validation for the above water quality comparison for the two areas.

Details on how the Table II illustrated Uranium ore grade values were estimated are provided below.






Table I

The economic evaluation of the Roca Honda uranium resource was prepared under the supervision of Stuart E. Collins of Roscoe Postle (USA) Ltd., Lakewood, Colorado. Mr. Collins is a Registered Professional Mining Engineer in the state of Colorado, and is a registered member of the Society for Mining and Metallurgy, and Exploration, and an independent and Qualified Person as defined in NI 43-101.

Summary of Roca Honda Mineral Resources as at August 9, 2011: Measured and Indicated Resources:

Classification	Tons	Grade % U ₃ O ₈	Lb U ₃ O ₈
Measured	284,000	0.395	2,247,000
Indicated	1,793,000	0.405	14,536,000
Total M+I	2,077,000	0.404	16,783,000
Inferred Resource:			
Classification	Tons	Grade % U ₃ O ₈	Lb U ₃ O ₈
Inferred	1,448,000	0.411	11,894,000

Notes:

- 1. CIM definitions were followed for Mineral Resources:
- 2. The Qualified Person for this Mineral Resource estimate is Patti Nakai-Lajoie, P.Geo.
- Mineral Resources are estimated using a cut-off grade of 0.13% U3O8.
- 4. A minimum mining thickness of six feet was used.
- 5. Numbers may not add due to rounding.

The modeling and estimation of the uranium resources were prepared under the supervision of Patti Nakai-Lajoie, P.Geo. and Principal Geologist, RPA. Ms. Nakai-Lajoie is a Professional Geoscientist in the Province of Ontario and an independent and Qualified Person as defined in NI 43-101. Ms. Nakai-Lajoie visited the Roca Honda Property on May 10-12, 2011 and is of the opinion that the data verification procedures support the geologic interpretations and confirm the quality of the database. It should be noted that mineral resources, which are not mineral reserves, do not have demonstrated economic viability.





Table II.- Summary of Highest Uranium Ore Grade Values Estimated from GR Log Readings for the Selected Garcia Hill Area Wells

	GH W-24	Garcia 2699	Garcia 2657	MW-86	Garcia 2722	Garcia 5	Garcia 1	MW-84		Expl G1607	Expl G1619	Expl G1622
Ft From GH W-24 (approx.)	0	547	681	739	787	915	1207	1302	Ft From GH W-20 (approx.)	550	335	2500
"B" Sand Interval?	Yes 508 - 621	Yes 562 - 633	Yes 550 - 634	Yes 535 - 629	Yes 538 - 606	Yes 555 - 628	Yes 530 - 600	Yes 538 - 615				
"B" Sand Highst. Ore Grade Read (%eU3O8)	0.0030 @ 575.0	<mark>0.0062</mark> @ 573.5	Essentially Flat GR Curve	0.0025 @ 564.5	0.0281 @ 554.5	Essentially Flat GR Curve	0.0071 @ 554.0	0.0076 @ 577.0	"B" Sand Highst. Ore Grade Read (%eU3O8)	0.0100 @ 553.5	<mark>0.0229</mark> @ 572.0	0.1572 @ 585.5
"A" Sand Interval?	Yes 625 - 691	Yes 643 - 705	Yes 640 - 663	Yes 640 - 670	Yes 611 - 650	Yes 640 - 692	Yes 611 - 678	Yes 661 - 675				
"A" Sand Highst. Ore Grade Read (%eU3O8)	Essentially Flat GR Curve											
"AA" Sand Interval?	Yes 695 - 747	Yes 709 - 780	Yes 692 - 761	Yes 688 - 719	Yes 686 - 780	Yes 695 - 750	Yes 681 - 762	Yes 678 - 773				
"AA" Sand Highst. Ore Grade Read (%eU3O8)	Essentially Flat GR Curve	0.0035 @737.5	0.0055 @ 746.5	Essentially Flat GR Curve	"AA" Sand Highst. Ore Grade Read (%eU3O8)	0.0438 @ 729.0	<mark>0.0071</mark> @ 726.0					
Initial U mg/L	0.032 0.011	Drilled & Abandoned	Drilled & Abandoned	0.019	Drilled & Abandoned	Drilled & Abandoned	Drilled & Abandoned	0.031		Drilled & Abandoned	Drilled & Abandoned	PA-3 Producer 13222?

Figure 3







Figure 5

Uranium concentrations in water samples from the **North Monitoring Wells** (the closest to Garcia Hill and to this work's selected wells) stood at near or below the standard of 30 µg/L.



Pre-Mining Uranium Concentrations in PA-3's Northernmost Monitoring Wells

Monitoring Well Number	Baseline Uranium Concentration
	mg/L
MW-81	0.017
MW-82	0.019
MW-83	0.031
MW-84	0.031
MW-85	0.018
MW-86	0.019
MW-87	0.025
Source: Handwritten r	notes on Operator provided map

One Rare Analysis for Uranium for a City of Kingsville's Public Water Supply Well



Safe Drinking Water Information System (SDWIS)


Report generated on: 9/12/2012

 Radionuclide Results Report: CITY OF KINGSVILLE PWSID TX1370001 for samples collected between 1/1/2000 and 9/12/2012

Report Description: Detailed Radionuclide result for a system by entry point and sample given a user defined date range and PWS ID.

TCEQ ID	LAB ID	TEST NAME	RESULT UNIT OF ME	SAMPLE DATE	SYSTEM ID	CONT ID	POC 1
1153870	AB54309	Gross Alpha, Incl. Radon & U	15.4 pCi/L	04/20/2011	1370001	4002	EP004
1153870	AB54309	Gross Beta Particle Activity	7.4 pCi/L	04/20/2011	1370001	4100	EP004
1153870	AB54309	Radium-226	Non-Detect	04/20/2011	1370001	4020	EP004
1153870	AB54309	Radium-228	Non-Detect	04/20/2011	1370001	4030	EP004
1153870	AB54309	Uranium-238 ←	2.7 pCi/L	04/20/2011	1370001	4009	EP004
1153870	AB54309	Uranium-234 ←	6.5 pCi/L	04/20/2011	1370001	4007	EP004
1153870	AB54309	Uranium-235 ←	Non-Detect	04/20/2011	1370001	4008	EP004
	10000000000000000000000000000000000000	Combined Uranium	8.0 µg/L				
		Gross Alpha, Excl. Radon & U	10.0 pCi/L				
		Combined Radium (-226 & -228)	Non-Detect				
0828826	AA51939	Gross Alpha, Incl. Radon & U	10.1 pCi/L	02/12/2008	1370001	4002	EP004
0828826	AA51939	Gross Beta Particle Activity	5.4 pCi/L	02/12/2008	1370001	4100	EP004
0828826	AA51939	Radium-226	Non-Detect	02/12/2008	1370001	4020	EP004
0828826	AA51939	Radium-228	Non-Detect	02/12/2008	1370001	4030	EP004
		Combined Radium (-226 & -228)	Non-Detect				
0525248	EP506258	Gross Beta Particle Activity	10.3 pCi/L	03/07/2005	1370001	4100	EP004
0525248	EP506258	Radium-226	Non-Detect	03/07/2005	1370001	4020	EP004
0525248	EP506258	Radium-228	Non-Detect	03/07/2005	1370001	4030	EP004
0525248	EP506258	Gross Alpha Particle Activity	11.9 pCi/L	03/07/2005	1370001	4109	EP004
	EP204782	Gross Beta Particle Activity	9.2 pCi/L	03/12/2002	1370001	4100	EP004
	EP204782	Radium-226	Non-Detect	03/12/2002	1370001	4020	EP004
	EP204782	Radium-228	Non-Detect	03/12/2002	1370001	4030	EP004
	EP204782	Gross Alpha Particle Activity	12.2 pCi/L	03/12/2002	1370001	4109	EP004

Figure 6 Stratigraphic Column/Completion Comparison for Garcia Hill W-24, W-25 and City of Kingsville PWS No. 7 Well



THE COMPUTATIONAL MODEL USED FOR ESTIMATING URANIUM ORE GRADE AS %U3O8

A SAMPLE COMPUTATION OF URANIUM ORE GRADE, USING THE BACKGROUND TO BACKGROUND METHOD, HAS BEEN IMPLEMENTED, AND THE RESULTS HAVE BEEN COMPARED AGAINST THE AVAILABLE RESULTS FROM ANOTHER COMMERCIAL COMPUTER PROGRAM FOR VALIDATION OF THE PROCEDURE USED IN THIS WORK. DETAILS ON THESE COMPUTATIONS ARE PRESENTED BELOW.

The numerical results for an assay by COMPUTER LOGGING INCORPORATED for the KVD area Adami No. 2 Well were faithfully duplicated by the computer routine used in this work, as can be seen in Tables IV and V. The curve in Figure 7 is the graphic representation of the digitized GR data, which was used as input.

The same computational scheme was used for all of the other assays, which were completed for the 11 selected KVD area wells. The map in Figure 1 identifies these wells and illustrates their location. These wells' GR Logs were digitized by taking readings every six inches across the selected depth interval, and tabulating them. The tabulated readings were later put in a graph for comparison with the recorded log curve as a quality assurance exercise.

Tables VI through XVIII show the input GR readings and the computed %U3O8 values. These results are for eligible "B" and "AA" Sands intervals when present in the selected wells. Figures 8 through 33 illustrate the recorded GR and digitized curves. Alternating with these curves are graphic comparisons of the %U3O8 values, computed across the selected depth interval, against the set cut-off ore grade values for mining, one of the main objectives of this work.

Comparison of the highest ore grade readings against the set cut-off values for mining was illustrated at the beginning of this discussion (Figure 3) to call attention to the natural correlation between very low Uranium ore grade and drinkable water.

COMPUTER LOGGING INCORPORATED

Table IV

URANIUM DATA ANALYSIS


CLIENT: HOLE NO: DATE:	U.R.T. ADAMI‡ 12-07-	‡ 2						%U3O8
K-FACTOR= CORRECTIO				DEADTIME	(MICROSE	D.)= .000	000025	HOLE SIZE AND
DEPTH (FT)	RAW CPS	CORRECTED CPS		CUT #1 .020			CUT #4	WATER CORR. GRADE
662.0	194,	194.	.003					0.0028
662.5	and the said H	223.	.003					0.0033
	266.	266.	. 004					0.0039
663,5	353.	355	., 005					0.0052
664.0	638,	638.	. 009					0.0093
664.5	1170.	1171	. O17					0.0171
665,0	1649.	1650.	.024	.024				0.0242
665.5	1809.	1810.	.026	.026				0.0265
666.0	1686,	1686.	.024	.024				0.0247
666.5	1618.	1619.	,023	,023				0.0237
667.0	1789.	1790.	.026	.026				0.0262
667.5	2255.	20 (20 (m) "Y n	.033	EEQ.				0.0330
668.0	2321.	And add the file is	.034	"O34				0.0340
668.5	1692	1692.	,025	.025				0.0248
669.0	999.	999.	.014					0.0146
669.5	603.	604.	, 009					0.0088
	467 .	467.	.007					0.0068
670.5	397.	397.	. 006					0.0058

CUTOFF NUMBER 1

NUMBER OF HALF-FOOT INTERVALS: AVERAGE GRADE= .027

GRADE-THICKNESS PRODUCT= . . 107

Figure 7



ORE GRADE AND GRADE-THICKNESS CALCULATION Background to Background Method (Continues)

Given Data					
Data Entered by Logger					
Calculated Data					
DATE: WELL NAME: LOGGING ENGINEER: UNIT No.:	Adami No. 2				
PROBE No.:					
INTERVAL: Ft	0.5				
BIT SIZE: in Inches WATER IN HOLE? (Y/N)	5.125 y				
WATER CORRECTION:	1.14861875				
STEEL PIPE IN HOLE? (Y/N) THICKNESS: in Inches	n 1				
STEEL CORRECTION:	1				
DEAD TIME: K FACTOR:	2.50000E-07 6.30000E-06				
			GRADE=	0.01714317	%eU308
			GRADE-THICKNESS=	0.14571697	
Interval Of Interest:	662.00	to		670.50	
KVD's PA-3 Adami No. 2					

ORE GRADE AND GRADE-THICKNESS CALCULATION (Concluded)


Background to Background Method

		•	<u> </u>			
KVD's PA-3 Adami No.	2					
					HOLE	
					SIZE	
DEPTH	GAMMA-HI			%eU308	AND	
DEITH	CPS		GAMMA-HI	RADIOMETRIC	WATER	STEEL CASING
	PROBE		CPS,	GRADE PER	CORR.	CORRECTED
	COUNTS		CORRECTED	UNIT	GRADE	GRADE
662.00	194.00		194.01	0.0024	0.0028	0.0028
662.50	223.00		223.01	0.0028	0.0033	0.0033
663.00	266.00		266.02	0.0034	0.0039	0.0039
663.50	353.00		353.03	0.0044	0.0052	0.0052
664.00	638.00		638.10	0.0080	0.0093	0.0093
664.50	1170.00		1170.34	0.0147	0.0171	0.0171
665.00	1649.00		1649.68	0.0208	0.0242	0.0242
665.50	1809.00		1809.82	0.0228	0.0265	0.0265
666.00	1686.00		1686.71	0.0213	0.0247	0.0247
666.50	1618.00		1618.65	0.0204	0.0237	0.0237
667.00	1789.00		1789.80	0.0226	0.0262	0.0262
667.50	2255.00		2256.27	0.0284	0.0330	0.0330
668.00	2321.00		2322.35	0.0293	0.0340	0.0340
668.50	1692.00		1692.72	0.0213	0.0248	0.0248
669.00	999.00		999.25	0.0126	0.0146	0.0146
669.50	603.00		603.09	0.0076	0.0088	0.0088
670.00	467.00		467.05	0.0059	0.0068	0.0068
670.50	397.00		397.04	0.0050	0.0058	0.0058

The Assay for the Garcia Hill W-24 Water Supply Well, initially identified as 1989 Exploratory Well Garcia 1627, is shown in Figures 8 and 9, and in Table VI.

Figure 9 illustrates the contrast between the estimated ore grade values across the "B" Sand in the W-24 well and the 0.11 %U3O8 and 0.13 %U3O8 curves, set as the cut-off values for mining.

Figure 8



ORE GRADE AND GRADE-THICKNESS CALCULATION

Background to Background Method

Table VI (Continues)

KVDs Garcia Hill W-24 - B S		ground to backgroun	a ivictioa			
DEPTH	GAMMA-HI CPS PROBE COUNTS	GAMMA-HI CPS, CORRECTED	%U3O8 RADIOMETRIC GRADE PER UNIT	HOLE SIZE AND WATER CORR. GRADE	STEEL CASING CORRECTED GRADE	
553.00	65.00	65.00	0.0008	0.0009	0.0009	
553.50	85.00	85.00	0.0010	0.0012	0.0012	
554.00	110.00	110.00	0.0014	0.0016	0.0016	
554.50	128.00	128.00	0.0016	0.0018	0.0018	
555.00	139.00	139.00	0.0017	0.0020	0.0020	
555.50	145.00	145.01	0.0018	0.0021	0.0021	
556.00	156.00	156.01	0.0019	0.0022	0.0022	
556.50	160.00	160.01	0.0020	0.0023	0.0023	
557.00	181.00	181.01	0.0022	0.0026	0.0026	
557.50	180.00	180.01	0.0022	0.0026	0.0026	
558.00	145.00	145.01	0.0018	0.0021	0.0021	
558.50	109.00	109.00	0.0013	0.0016	0.0016	
559.00	102.00	102.00	0.0013	0.0015	0.0015	
559.50	104.00	104.00	0.0013	0.0015	0.0015	
560.00	102.00	102.00	0.0013	0.0015	0.0015	
560.50	104.00	104.00	0.0013	0.0015	0.0015	
561.00	107.00	107.00	0.0013	0.0015	0.0015	
561.50	110.00	110.00	0.0014	0.0016	0.0016	
562.00	110.00	110.00	0.0014	0.0016	0.0016	
562.50	125.00	125.00	0.0015	0.0018	0.0018	
563.00	130.00	130.00	0.0016	0.0019	0.0019	
563.50	120.00	120.00	0.0015	0.0017	0.0017	
564.00	110.00	110.00	0.0014	0.0016	0.0016	
564.50	110.00	110.00	0.0014	0.0016	0.0016	
565.00	117.00	117.00	0.0014	0.0017	0.0017	

ORE GRADE AND GRADE-THICKNESS CALCULATION Background to Background Method

Table VI (Concluded)

VDs W-24 - "B" Sand				
565.00	117.00	117.00	0.0014 0.0017	0.0017
565.50	132.00	132.00	0.0016 0.0019	0.0019
566.00	164.00	164.01	0.0020 0.0024	0.0024
566.50	190.00	190.01	0.0023 0.0027	0.0027
567.00	187.00	187.01	0.0023 0.0027	0.0027
567.50	160.00	160.01	0.0020 0.0023	0.0023
568.00	157.00	157.01	0.0019 0.0023	0.0023
568.50	160.00	160.01	0.0020 0.0023	0.0023
569.00	168.00	168.01	0.0021 0.0024	0.0024
569.50	182.00	182.01	0.0022 0.0026	0.0026
570.00	175.00	175.01	0.0022 0.0025	0.0025
570.50	130.00	130.00	0.0016 0.0019	0.0019
571.00	110.00	110.00	0.0014 0.0016	0.0016
571.50	99.00	99.00	0.0012 0.0014	0.0014
572.00	93.00	93.00	0.0011 0.0013	0.0013
572.50	100.00	100.00	0.0012 0.0014	0.0014
573.00	109.00	109.00	0.0013 0.0016	0.0016
573.50	140.00	140.00	0.0017 0.0020	0.0020
574.00	175.00	175.01	0.0022 0.0025	0.0025
574.50	204.00	204.01	0.0025 0.0029	0.0029
575.00	211.00	211.01	0.0026 0.0030	0.0030
575.50	204.00	204.01	0.0025 0.0029	0.0029
576.00	180.00	180.01	0.0022 0.0026	0.0026
576.50	160.00	160.01	0.0020 0.0023	0.0023
577.00	115.00	115.00	0.0014 0.0017	0.0017
577.50	75.00	75.00	0.0009 0.0011	0.0011
	0000			
	AREA	6834.25	i i	
	DEPTH MAX			
553.00	DEPTH MIN			

Figure 9



The Assay for the Exploratory Garcia 2699 Well, "B" Sand, is shown in Figures 10 and 11, and in Table VII.

Figure 11 illustrates the spread between the estimated ore grade values across the "B" Sand in the Garcia 2699 Well, and the 0.11 %U3O8 and 0.13 %U3O8 curves, the set cut-off values for mining.


Figure 10

ORE GRADE AND GRADE-THICKNESS CALCULATION Background to Background Method

Table VII

			O				
Given Data							
Data Entered by Logger							
Calculated Data							
DATE:	12/27/1996						
WELL NAME:	Garcia 2699						
LOGGING ENGINEER:							
UNIT No.:							
PROBE No.:							
INTERVAL: Ft	0.5						
BIT SIZE: in Inches	6.750						
WATER IN HOLE? (Y/N)	У						
WATER CORRECTION:	1.2080125						
STEEL PIPE IN HOLE? (Y/N)	n						
THICKNESS: in Inches	1						
STEEL CORRECTION:	1						
DEAD TIME:	2.30000E-07						
K FACTOR:	5.73000E-06						
KVDs Expl. Garcia 2699							
		GRADE=	0.0062130	%eU308			
		GRADE-THICKNESS=	0.0124259				
Interval Of Interest:	572.00	to	574.00				
					HOLE		
	GAMMA-HI			%U3O8	SIZE		
DEPTH	CPS		GAMMA-HI	RADIOMETRIC	AND		
	PROBE		CPS,	GRADE PER	WATER	STEEL CASING	
	COUNTS		CORRECTED	UNIT	CORR.	CORRECTION	
572.00	215.00		215.01	0.0025	0.0030	0.0030	
572.50	340.00		340.03	0.0039	0.0047	0.0047	
573.00	442.00		442.04	0.0051	0.0061	0.0061	
573.50	450.00		450.05	0.0052	0.0062	0.0062	
574.00	348.00		348.03	0.0040	0.0048	0.0048	
	THE REAL PROPERTY CO.						


Figure 11



The Assay for the Exploratory Garcia 2699 Well, "AA" Sand, is shown in Figures 12 and 13, and in Table VIII.

Figure 13 illustrates the spread between the estimated ore grade values across the "AA" Sand in the Garcia 2699 Well, and the 0.11 %U3O8 and 0.13 %U3O8 curves, the set cut-off values for mining.

Figure 12



KVD's Expl. Garcia 2699 - "AA" Sand - GR Recorded & Digitized Curves Comparison


ORE GRADE AND GRADE-THICKNESS CALCULATION

Background to Background Method

Table VIII


nun n 1 acco		u to background			
CVDs Garcia 2699 - AA Sand DEPTH	GAMMA-HI CPS PROBE COUNTS	GAMMA-HI CPS, CORRECTED	%U3O8 RADIOMETRIC GRADE PER UNIT	HOLE SIZE AND WATER CORR. GRADE	STEEL CASING CORRECTED GRADE
729.00	39.00	39.00	0.0004	0.0005	0.0005
729.50	44.00	44.00	0.0005	0.0006	0.0006
730.00	46.00	46.00	0.0005	0.0006	0.0006
730.50	51.00	51.00	0.0006	0.0007	0.0007
731.00	66.00	66.00	0.0008	0.0009	0.0009
731.50	67.00	67.00	0.0008	0.0009	0.0009
732.00	50.00	50.00	0.0006	0.0007	0.0007
732.50	53.00	53.00	0.0006	0.0007	0.0007
733.00	88.00	88.00	0.0010		0.0012
733.50	131.00	131.00	0.0015	0.0018	0.0018
734.00	159.00	159.01	0.0018	0.0022	0.0022
734.50	175.00	175.01	0.0020	0.0024	0.0024
735.00	197.00	197.01	0.0023	0.0027	0.0027
735.50	185.00	185.01	0.0021	0.0026	0.0026
736.00	194.00	194.01	0.0022	0.0027	0.0027
736.50	213.00	213.01	0.0024	0.0029	0.0029
737.00	224.00	224.01	0.0026	0.0031	0.0031
737.50	254.00	254.01	0.0029	0.0035	0.0035
738.00	233.00	233.01	0.0027	0.0032	0.0032
738.50	211.00	211.01	0.0024	0.0029	0.0029
739.00	179.00	179.01	0.0021	0.0025	0.0025
739.50	167.00	167.01	0.0019	0.0023	0.0023
740.00	139.00	139.00	0.0016	0.0019	0.0019
740.50	118.00	118.00	0.0014	0.0016	0.0016
741.00	90.00	90.00	0.0010	0.0012	0.0012
741.50	80.00	80.00	0.0009	0.0011	0.0011
742.00	76.00	76.00	0.0009	0.0011	0.0011
742.50	65.00	65.00	0.0007	0.0009	0.0009
743.00	58.00	58.00	0.0007	0.0008	0.0008
743.50	49.00	49.00	0.0006	0.0007	0.0007
744.00	44.00	44.00	0.0005	0.0006	0.0006
744.50	51.00	51.00	0.0006	0.0007	0.0007
745.00	58.00	58.00	0.0007	0.0008	0.0008
745.50	47.00	47.00	0.0005	0.0007	0.0007
746.00	43.00	43.00	0.0005	0.0006	0.0006
746.50	57.00	57.00	0.0007	0.0008	0.0008
747.00	64.00	64.00	0.0007	0.0009	0.0009

Figure 13



The Assay for the Exploratory Garcia 2657 Well, "AA" Sand, is shown in Figures 14 and 15, and in Table IX.

Figure 15 illustrates the spread between the estimated ore grade values across the "AA" Sand in the Garcia 2657 Well, and the 0.11 %U3O8 and 0.13 %U3O8 curves, the set cut-off values for mining.



KVD's Expl. Garcia 2657 - "AA" Sand - Recorded & Digitized GR Curves Comparison

ORE GRADE AND GRADE-THICKNESS CALCULATION

Background to Background Method

Table IX (Continues)


KVDs Garcia 2647 - AA Sand		ind to backgro			
DEPTH	GAMMA-HI CPS PROBE COUNTS	GAMMA-HI CPS, CORRECTED	%U3O8 RADIOMETRIC GRADE PER UNIT	HOLE SIZE AND WATER CORR. GRADE	STEEL CASING CORRECTED GRADE
726.00	53.00	53.00		0.0008	0.0008
726.50	54.00	54.00		0.0008	0.0008
727.00	62.00	62.00	0.0008	0.0009	0.0009
727.50	62.00	62.00	0.0008	0.0009	0.0009
728.00	62.00	62.00	0.0008	0.0009	0.0009
728.50	75.00	75.00		0.0011	0.0011
729.00	102.00	102.00	0.0013	0.0015	0.0015
729.50	102.00	102.00	0.0013	0.0015	0.0015
730.00	85.00	85.00		0.0013	0.0012
730.50	70.00	70.00	0.0009	0.0010	0.0010
731.00	80.00	80.00	0.0010	0.0012	0.0012
731.50	115.00	115.00		0.0017	0.0017
732.00	115.00	115.00		0.0017	0.0017
732.50	116.00	116.00		0.0017	0.0017
733.00	138.00	138.00		0.0020	0.0020
733.50	145.00	145.01	0.0018	0.0021	0.0021
734.00	165.00	165.01	0.0020	0.0024	0.0024
734.50	237.00	237.01		0.0034	0.0034
735.00	255.00	255.02	0.0031	0.0037	0.0037
735.50	233.00	233.01	0.0029	0.0034	0.0034
736.00	243.00	243.01		0.0035	0.0035
736.50	250.00	250.02		0.0036	0.0036
737.00	212.00	212.01		0.0031	0.0031
737.50	183.00	183.01		0.0026	0.0026
738.00	210.00	210.01	0.0026	0.0030	0.0030
738.50	270.00	270.02	0.0033	0.0039	0.0039
739.00	278.00	278.02		0.0040	0.0040
739.50	260.00	260.02		0.0037	0.0037
740.00	253.00	253.02	0.0031	0.0036	0.0036
740.50	273.00	273.02		0.0039	0.0039
741.00	270.00	270.02	0.0033	0.0039	0.0039
741.50	238.00	238.01	0.0029	0.0034	0.0034
742.00	265.00	265.02	0.0033	0.0038	0.0038
742.50	264.00	264.02		0.0038	0.0038
743.00	220.00	220.01		0.0032	0.0032
743.50	215.00	215.01		0.0031	0.0031
744.00	235.00	235.01		0.0034	0.0034

ORE GRADE AND GRADE-THICKNESS CALCULATION Background to Background Method

Table IX (Concluded)

KVD's Expl. Garcia 2657				
744.00 235.00	235.01	0.0029 0.0034	0.0034	
744.50 265.00	265.02	0.0033 0.0038	0.0038	
745.00 280.00	280.02	0.0035 0.0040	0.0040	
745.50 335.00	335.03	0.0041 0.0048	0.0048	
746.00 372.00	372.03	0.0046 0.0054	0.0054	
746.50 380.00	380.04	0.0047 0.0055	0.0055	
747.00 260.00	260.02	0.0032 0.0037	0.0037	
747.50 195.00	195.01	0.0024 0.0028	0.0028	
748.00 240.00	240.01	0.0030 0.0035	0.0035	
748.50 234.00	234.01	0.0029 0.0034	0.0034	
749.00 198.00	198.01	0.0024 0.0029	0.0029	
749.50 193.00	193.01	0.0024 0.0028	0.0028	
750.00 160.00	160.01	0.0020 0.0023	0.0023	
750.50 142.00	142.01	0.0018 0.0020	0.0020	
751.00 132.00	132.00	0.0016 0.0019	0.0019	
751.50 137.00	137.00	0.0017 0.0020	0.0020	
752.00 120.00	120.00	0.0015 0.0017	0.0017	
752.50 110.00	110.00	0.0014 0.0016	0.0016	
753.00 110.00	110.00	0.0014 0.0016	0.0016	
753.50 120.00	120.00	0.0015 0.0017	0.0017	
754.00 137.00	137.00	0.0017 0.0020	0.0020	
754.50 145.00	145.01	0.0018 0.0021	0.0021	
755.00 140.00	140.00	0.0017 0.0020	0.0020	
755.50 160.00	160.01	0.0020 0.0023	0.0023	
756.00 160.00	160.01	0.0020 0.0023	0.0023	
756.50 160.00	160.01	0.0020 0.0023	0.0023	
757.00 175.00	175.01	0.0022 0.0025	0.0025	
757.50 240.00	240.01	0.0030 0.0035	0.0035	
758.00 262.00	262.02	0.0032 0.0038	0.0038	
758.50 200.00	200.01	0.0025 0.0029	0.0029	
759.00 145.00	145.01	0.0018 0.0021	0.0021	
759.50 140.00	140.00	0.0017 0.0020	0.0020	
760.00 170.00	170.01	0.0021 0.0024	0.0024	
760.50 203.00	203.01	0.0025 0.0029	0.0029	
761.00 185.00	185.01	0.0023 0.0027	0.0027	
761.50 135.00	135.00	0.0017 0.0019	0.0019	
762.00 60.00	60.00	0.0007 0.0009	0.0009	


Figure 15



The Assay for KVD's PA-3 MW-86, "B" Sand, is shown in Figures 16 and 17, and in Table X.


Figure 17 illustrates the spread between the estimated ore grade values across the "B" Sand in the MW-86 Well, and the 0.11 %U3O8 and 0.13 %U3O8 curves, the set cut-off values for mining.

Figure 16




/Ds PA-3 MW-86						
DEPTH	GAMMA-HI CPS PROBE COUNTS	GAMMA-HI CPS, CORRECTED	%U3O8 RADIOMETRIC GRADE PER UNIT	HOLE SIZE AND WATER CORR. GRADE	STEEL CASING CORRECTED GRADE	
562.00	85.00	85.00	0.0010	0.0011	0.0011	
562.50	110.00	110.00	0.0013	0.0015	0.0015	
563.00	150.00	150.01	0.0017	0.0020	0.0020	
563.50	185.00	185.01	0.0021	0.0025	0.0025	
564.00	185.00	185.01	0.0021	0.0025	0.0025	
564.50	185.00	185.01	0.0021	0.0025	0.0025	
565.00	185.00	185.01	0.0021	0.0025	0.0025	
565.50	160.00	160.01	0.0018	0.0021	0.0021	
566.00	175.00	175.01	0.0020	0.0023	0.0023	
566.50	185.00	185.01	0.0021	0.0025	0.0025	
567.00	165.00	165.01	0.0019	0.0022	0.0022	
567.50	130.00	130.00	0.0015	0.00174	0.0017	
568.00	105.00	105.00	0.0012	0.0014	0.0014	
568.50	90.00	90.00	0.0010	0.0012	0.0012	

Figure 17



The Assay for KVD's Exploratory Garcia 2722, "B" Sand, is shown in Figures 18 and 19, and in Table XI.


Figure 19 illustrates the spread between the estimated ore grade values across the "B" Sand in the Garcia 2722 Well, and the 0.11 %U3O8 and 0.13 %U3O8 curves, the set cut-off values for mining.



KVD's Exploratory Garcia 2722 Well - "B" Sand – GR Recorded & Digitized Curves Comparison

Garcia 2722 - B Sanc					
DEPTH	GAMMA-HI CPS PROBE COUNTS	GAMMA-HI CPS, CORRECTED	%U3O8 RADIOMETRIC GRADE PER UNIT	HOLE SIZE AND WATER CORR. GRADE	STEEL CASING CORRECTED GRADE
545.50	1003.33	1003.58	0.0121	0.0141	0.0141
546.00	1353.33	1353.78	0.0163	0.0190	0.0190
546.50	1796.67	1797.46	0.0216	0.0253	0.0253
547.00	1943.33	1944.26	0.0234	0.0273	0.0273
547.50	1856.67	1857.51	0.0224	0.0261	0.0261
548.00	1763.33	1764.10	0.0212	0.0248	0.0248
548.50	1743.33	1744.08	0.0210	0.0245	0.0245
549.00	1716.67	1717.39	0.0207	0.0241	0.0241
549.50	1606.67	1607.30	0.0194	0.0226	0.0226
550.00	1393.33	1393.81	0.0168	0.0196	0.0196
550.50	1190.00	1190.35	0.0143	0.0167	0.0167
551.00	1106.67	1106.97	0.0133	0.0156	0.0156
551.50	1190.00	1190.35	0.0143	0.0167	0.0167
552.00	1353.33	1353.78	0.0163	0.0190	0.0190
552.50	1536.67	1537.25	0.0185	0.0216	0.0216
553.00	1690.00	1690.70	0.0204	0.0238	0.0238
553,50	1823.33	1824.15	0.0220	0.0256	0.0256
554.00	1960.00	1960.94	0.0236	0.0276	0.0276
554.50	2033.33	2034.35	0.0245	0.0286	0.0286
555.00	1803.33	1804.13	0.0217	0.0253	0.0253
555.50	1506.67	1507.22	0.0181	0.0212	0.0212
556.00	1180.00	1180.34	0.0142	0.0166	0.0166
556.50	900.00	900.20	0.0108	0.0126	0.0126


Figure 19



The Assay for KVD's Exploratory Garcia 1, "B" Sand, is shown in Figures 20 and 21, and in Table XII.

Figure 21 illustrates the spread between the estimated ore grade values across the "B" Sand in the Garcia 1 Well, and the 0.11 %U3O8 and 0.13 %U3O8 curves, the set cut-off values for mining.

Figure 20




KVD's ExplG1 - "B" Sand - GR Log - Recorded & Digitized Curves Comparison

Table XII

KVDs Expl. Garcia 1						
DEPTH	GAMMA-HI CPS	GAMMA-HI	%U3O8 RADIOMETRI	HOLE SIZE AND WATER	STEEL CASING	
	PROBE COUNTS	CPS,	C GRADE PER UNIT	CORR.	CORRECTED	
547.00	110.00	110.00		0.0017		
547.50	117.00	117.00		0.0017		
548.00	132.00	132.00		0.0020		
548.50	180.00	180.01		0.0028		
549.00	235.00	235.01		0.0036		
549.50	245.00	245.01	0.0033	0.0038	0.0038	
550.00	242.00	242.01	0.0032	0.0038	0.0038	
550.50	225.00	225.01	0.0030	0.0035	0.0035	
551.00	210.00	210.01	0.0028	0.0033	0.0033	
551.50	212.00	212.01	0.0028	0.0033	0.0033	
552.00	215.00	215.01	0.0029	0.0033	0.0033	
552.50	225.00	225.01	0.0030	0.0035	0.0035	
553.00	250.00	250.01	0.0033	0.0039	0.0039	
553.50	390.00	390.03		0.0061	0.0061	
554.00	460.00	460.05		0.0071	0.0071	
554.50	430.00	430.04		0.0067		
555.00	300.00	300.02		0.0047		
555.50	245.00	245.01		0.0038		
556.00	250.00	250.01		0.0039		
556.50	265.00	265.02		0.0041		
557.00	230.00	230.01		0.0036		
557.50	170.00	170.01		0.0026		
558.00	165.00	165.01		0.0026		
558.50	180.00	180.01		0.0028		
559.00 559.50	195.00 205.00	195.01		0.0030		
560.00	220.00	205.01 220.01		0.0034		
560.50	227.00	227.01		0.0034		
561.00	225.00	225.01		0.0035		
561.50	238.00	238.01		0.0037		
562.00	225.00	225.01		0.0037		
562.50	210.00	210.01		0.0033		
563.00	215.00	215.01		0.0033		
563.50	215.00	215.01		0.0033		
564.00	212.00	212.01		0.0033		
564.50	212.00	212.01	0.0028	0.0033	0.0033	
565.00	212.00	212.01	0.0028	0.0033	0.0033	
565.50	175.00	175.01	0.0023	0.0027	0.0027	
566.00	175.00	175.01	0.0023	0.0027	0.0027	
566.50	188.00	188.01	0.0025	0.0029	0.0029	
567.00	191.00	191.01	0.0026	0.0030	0.0030	
567.50	191.00	191.01	0.0026	0.0030	0.0030	
568.00	195.00	195.01	0.0026	0.0030	0.0030	
568.50	175.00	175.01	0.0023	0.0027	0.0027	
569.00	159.00	159.01		0.0025		
569.50		162.01		0.0025		
570.00	170.00	170.01	0.0023	0.0026	0.0026	

Figure 21



The Assay for KVD's PA-3 MW84, "B" Sand, is shown in Figures 22 and 23, and in Table XIII.

Figure 23 illustrates the spread between the estimated ore grade values across the "B" Sand in the PA-3 MW84 Well, and the 0.11 %U3O8 and 0.13 %U3O8 curves, the set cut-off values for mining.

Figure 22





Table XIII (Continues)

KVDs PA-3 MW-84					
DEPTH	GAMMA-HI CPS	GAMMA-HI	%U3O8 RADIOMETRIC		STEEL CASING
	PROBE	CPS,	GRADE PER UNIT	CORR. GRADE	CORRECTED GRADE
553.00	75.00	75.00	0.0008	0.0010	0.0010
553.50	73.00	 73.00	0.0008	0.0010	0.0010
554.00	69.00	69.00	0.0007	0.0009	0.0009
554.50	73.00	73.00	0.0008	0.0010	0.0010
555.00	73.00	73.00	0.0008	0.0010	0.0010
555.50	100.00	100.00	0.0011	0.0013	0.0013
556.00	120.00	120.00	0.0013	0.0016	0.0016
556.50	128.00	128.00	0.0014	0.0017	0.0017
557.00	130.00	130.00	0.0014	0.0017	0.0017
557.50	135.00	135.00	0.0014	0.0018	0.0018
558.00	190.00	190.01	0.0020	0.0025	0.0025
558.50	215.00	215.01	0.0023	0.0029	0.0029
559.00	230.00	230.01	0.0025	0.0031	0.0031
559.50	250.00	250.02	0.0027	0.0033	0.0033
560.00	200.00	200.01	0.0021	0.0027	0.0027
560.50	170.00	170.01	0.0018	0.0023	0.0023
561.00	195.00	195.01	0.0021	0.0026	0.0026
561.50	195.00	195.01	0.0021	0.0026	0.0026
562.00	185.00	185.01	0.0020	0.0025	0.0025
562.50	165.00	165.01	0.0018	0.0022	0.0022
563.00	190.00	190.01	0.0020	0.0025	0.0025
563.50	200.00	200.01	0.0021		0.0027
564.00	240.00	240.02	0.0026	0.0032	0.0032
564.50	250.00	250.02	0.0027	0.0033	0.0033
565.00	300.00	300.02	0.0032	0.0040	0.0040
565.50	350.00	350.03	0.0037	0.0047	0.0047
566.00	380 00	380 04	0.0041	0.0051	0.0051

Table XIII (Concluded)


566.50 350.00 350.03 0.0037 0.0047 0.0047 567.00 340.00 340.33 0.0036 0.0045 0.0045 567.50 345.00 345.03 0.0037 0.0046 0.0046 568.00 275.00 275.02 0.0029 0.0037 0.0037 568.50 270.00 270.02 0.0029 0.0036 0.0036 569.00 260.00 260.02 0.0028 0.0035 0.0035 570.00 290.00 290.02 0.0031 0.0039 0.0039 570.00 290.00 290.02 0.0031 0.0039 0.0039 571.00 285.00 285.02 0.0030 0.0038 0.0035 572.00 230.00 230.01 0.0025 0.0031 0.0031 572.50 240.00 240.02 0.0026 0.0032 0.0032 573.00 270.00 270.02 0.0029 0.0036 0.0036 574.50 370.00 370.04	KVD's PA-3 MW84					
567.50 345.00 345.03 0.0037 0.0046 0.0046 568.00 275.00 275.02 0.0029 0.0037 0.0036 568.50 270.00 270.02 0.0029 0.0036 0.0036 569.50 270.00 260.02 0.0028 0.0035 0.0035 570.00 290.00 290.02 0.0031 0.0039 0.0039 570.50 325.00 325.03 0.0035 0.0043 0.0043 571.50 260.00 285.02 0.0030 0.0038 0.0038 572.00 230.00 280.01 0.0028 0.0035 0.0035 572.50 240.00 240.02 0.0028 0.0031 0.0031 573.00 270.00 270.02 0.0028 0.0035 0.0035 573.50 370.00 370.04 0.0040 0.0049 0.0032 574.00 370.00 370.04 0.0040 0.0049 0.0049 575.00 355.00 355.03	566.50	350.00	350.03	0.0037	0.0047	0.0047
568.00 275.00 275.02 0.0029 0.0037 0.0036 568.50 270.00 270.02 0.0029 0.0036 0.0036 569.00 260.00 260.02 0.0028 0.0035 0.0035 569.50 270.00 270.02 0.0029 0.0036 0.0036 570.00 290.02 0.0031 0.0039 0.0039 570.50 325.00 325.03 0.0035 0.0043 571.00 285.00 285.02 0.0030 0.0038 0.0038 571.50 260.00 260.02 0.0028 0.0035 0.0035 572.00 230.00 230.01 0.0025 0.0031 0.0031 572.50 240.00 240.02 0.0026 0.0032 0.0032 573.50 370.00 370.04 0.0049 0.0049 574.00 370.00 370.04 0.0040 0.0049 574.50 355.00 355.03 0.0038 0.0047 575.00	567.00	340.00	340.03	0.0036	0.0045	0.0045
568.50 270.00 270.02 0.0029 0.0036 0.0035 569.00 260.00 260.02 0.0028 0.0035 0.0035 569.50 270.00 270.02 0.0029 0.0036 0.0036 570.00 290.00 290.02 0.0031 0.0039 0.0039 570.50 325.00 325.03 0.0035 0.0043 0.0043 571.00 285.00 285.02 0.0030 0.0038 0.0035 571.50 260.00 260.02 0.0028 0.0035 0.0035 572.00 230.00 230.01 0.0025 0.0031 0.0031 572.50 240.00 240.02 0.0026 0.0032 0.0032 573.00 270.00 270.02 0.0029 0.0036 0.0036 573.50 370.00 370.04 0.0040 0.0049 0.0049 574.00 370.00 370.04 0.0040 0.0049 0.0049 575.00 310.00 310.03	567.50	345.00	345.03	0.0037	0.0046	0.0046
569.00 260.00 260.02 0.0028 0.0035 0.0036 569.50 270.00 270.02 0.0029 0.0036 0.0036 570.00 290.00 290.02 0.0031 0.0039 0.0039 570.50 325.00 325.03 0.0035 0.0043 0.0043 571.00 285.00 285.02 0.0030 0.0038 0.0035 572.00 230.00 260.02 0.0028 0.0035 0.0035 572.00 230.00 230.01 0.0025 0.0031 0.0031 572.50 240.00 240.02 0.0026 0.0032 0.0032 573.00 270.00 270.02 0.0029 0.0036 0.0036 573.50 370.00 370.04 0.0040 0.0049 0.0049 574.00 370.00 370.04 0.0040 0.0049 0.0049 574.50 355.00 355.03 0.0038 0.0047 0.0047 575.50 285.00 285.02	568.00	275.00	275.02	0.0029	0.0037	0.0037
569.50 270.00 270.02 0.0029 0.0036 0.0039 570.00 290.00 290.02 0.0031 0.0039 0.0039 570.50 325.00 325.03 0.0035 0.0043 0.0038 571.00 285.00 285.02 0.0030 0.0038 0.0035 571.50 260.00 260.02 0.0028 0.0035 0.0035 572.00 230.00 230.01 0.0025 0.0031 0.0031 572.50 240.00 240.02 0.0026 0.0032 0.0032 573.50 370.00 270.02 0.0029 0.0036 0.0036 574.50 370.00 370.04 0.0040 0.0049 0.0049 574.50 370.00 370.04 0.0040 0.0049 0.0049 574.50 355.00 355.03 0.0038 0.0047 0.0047 575.50 285.00 285.02 0.0030 0.0038 0.0044 576.50 450.00 450.05	568.50	270.00	270.02	0.0029	0.0036	0.0036
570.00 290.00 290.02 0.0031 0.0039 0.0039 570.50 325.00 325.03 0.0035 0.0043 0.0043 571.00 285.00 285.02 0.0030 0.0038 0.0038 571.50 260.00 260.02 0.0028 0.0035 0.0035 572.00 230.00 230.01 0.0025 0.0031 0.0031 572.50 240.00 240.02 0.0026 0.0032 0.0032 573.00 270.00 270.02 0.0029 0.0036 0.0036 573.50 370.00 370.04 0.0040 0.0049 0.0049 574.00 370.00 370.04 0.0040 0.0049 0.0049 574.50 355.00 355.03 0.0038 0.0047 0.0047 575.00 310.00 310.03 0.0038 0.0041 0.0041 575.50 285.00 285.02 0.0030 0.0038 0.0038 576.00 330.00 330.03	569.00	260.00	260.02	0.0028	0.0035	0.0035
570.50 325.00 325.03 0.0035 0.0043 0.0043 571.00 285.00 285.02 0.0030 0.0038 0.0038 571.50 260.00 260.02 0.0028 0.0035 0.0035 572.00 230.00 230.01 0.0025 0.0031 0.0031 572.50 240.00 240.02 0.0026 0.0032 0.0032 573.00 270.00 270.02 0.0029 0.0036 0.0036 573.50 370.00 370.04 0.0040 0.0049 0.0049 574.00 370.00 370.04 0.0040 0.0049 0.0049 574.50 355.00 355.03 0.0038 0.0047 0.0047 575.50 310.00 310.03 0.0033 0.0041 0.0041 575.50 285.00 285.02 0.0030 0.0038 0.0038 576.00 330.00 330.03 0.0035 0.0044 0.0044 576.50 450.00 450.05 0.048 0.0060 0.0060 577.00 570.00 570.09 <th>569.50</th> <th>270.00</th> <th>270.02</th> <th>0.0029</th> <th>0.0036</th> <th>0.0036</th>	569.50	270.00	270.02	0.0029	0.0036	0.0036
571.00 285.00 285.02 0.0030 0.0038 0.0038 571.50 260.00 260.02 0.0028 0.0035 0.0035 572.00 230.00 230.01 0.0025 0.0031 0.0031 572.50 240.00 240.02 0.0026 0.0032 0.0032 573.00 270.00 270.02 0.0029 0.0036 0.0036 573.50 370.00 370.04 0.0040 0.0049 0.0049 574.00 370.00 370.04 0.0040 0.0049 0.0049 574.50 355.00 355.03 0.0038 0.0047 0.0047 575.00 310.00 310.03 0.0033 0.0041 0.0041 575.50 285.00 285.02 0.0030 0.0038 0.0038 576.00 330.00 330.03 0.0035 0.0044 0.0044 576.50 450.00 450.05 0.0048 0.0060 0.0060 577.00 570.00 570.09 0.0061 0.0076 0.0076 578.50 365.00 365.04 </th <th>570.00</th> <th>290.00</th> <th>290.02</th> <th>0.0031</th> <th>0.0039</th> <th>0.0039</th>	570.00	290.00	290.02	0.0031	0.0039	0.0039
571.50 260.00 260.02 0.0028 0.0035 0.0035 572.00 230.00 230.01 0.0025 0.0031 0.0031 572.50 240.00 240.02 0.0026 0.0032 0.0032 573.00 270.00 270.02 0.0029 0.0036 0.0036 573.50 370.00 370.04 0.0040 0.0049 0.0049 574.50 355.00 355.03 0.0038 0.0047 0.0047 575.50 310.00 310.03 0.0033 0.0041 0.0041 575.50 285.00 285.02 0.0030 0.0038 0.0038 576.00 330.00 330.03 0.0035 0.0044 0.0044 576.50 450.00 450.05 0.0048 0.0060 0.0060 577.00 570.00 570.09 0.0061 0.0076 0.0076 578.50 365.00 365.04 0.0039 0.0049 0.0049 579.50 215.00 275.02	570.50	325.00	325.03	0.0035	0.0043	0.0043
572.00 230.00 230.01 0.0025 0.0031 0.0032 572.50 240.00 240.02 0.0026 0.0032 0.0032 573.00 270.00 270.02 0.0029 0.0036 0.0036 573.50 370.00 370.04 0.0040 0.0049 0.0049 574.00 370.00 370.04 0.0040 0.0049 0.0049 574.50 355.00 355.03 0.0038 0.0047 0.0047 575.00 310.00 310.03 0.0033 0.0041 0.0041 575.50 285.00 285.02 0.0030 0.0038 0.0038 576.00 330.00 330.03 0.0035 0.0044 0.0044 576.50 450.00 450.05 0.0048 0.0060 0.0060 577.00 570.00 570.09 0.0061 0.0076 0.0076 578.50 365.00 365.04 0.0039 0.0049 0.0049 579.50 215.00 275.02	571.00	285.00	285.02	0.0030	0.0038	0.0038
572.50 240.00 240.02 0.0026 0.0032 0.0036 573.00 270.00 270.02 0.0029 0.0036 0.0036 573.50 370.00 370.04 0.0040 0.0049 0.0049 574.00 370.00 370.04 0.0040 0.0049 0.0049 574.50 355.00 355.03 0.0038 0.0047 0.0047 575.00 310.00 310.03 0.0033 0.0041 0.0041 575.50 285.00 285.02 0.0030 0.0038 0.0038 576.00 330.00 330.03 0.0035 0.0044 0.0044 576.50 450.00 450.05 0.0048 0.0060 0.0060 577.00 570.00 570.09 0.0061 0.0076 0.0076 578.50 365.00 365.04 0.0039 0.0049 0.0049 579.00 275.02 0.0029 0.0037 0.0037 579.50 215.00 215.01 0.0023	571.50	260.00	260.02	0.0028	0.0035	0.0035
573.00 270.00 270.02 0.0029 0.0036 0.0036 573.50 370.00 370.04 0.0040 0.0049 0.0049 574.00 370.00 370.04 0.0040 0.0049 0.0049 574.50 355.00 355.03 0.0038 0.0047 0.0047 575.00 310.00 310.03 0.0033 0.0041 0.0041 575.50 285.00 285.02 0.0030 0.0038 0.0038 576.00 330.00 330.03 0.0035 0.0044 0.0044 576.50 450.00 450.05 0.0048 0.0060 0.0060 577.00 570.00 570.09 0.0061 0.0076 0.0076 577.50 520.00 520.07 0.0056 0.0069 0.0069 578.00 460.00 460.06 0.0049 0.0061 0.0049 579.00 275.00 275.02 0.0029 0.0037 0.0037 579.50 215.00 215.01 0.0023 0.0023 0.0023 580.50 155.00 155.01 </th <th>572.00</th> <th>230.00</th> <th>230.01</th> <th>0.0025</th> <th>0.0031</th> <th>0.0031</th>	572.00	230.00	230.01	0.0025	0.0031	0.0031
573.50 370.00 370.04 0.0040 0.0049 0.0049 574.00 370.00 370.04 0.0040 0.0049 0.0049 574.50 355.00 355.03 0.0038 0.0047 0.0047 575.00 310.00 310.03 0.0033 0.0041 0.0041 575.50 285.00 285.02 0.0030 0.0038 0.0038 576.00 330.00 330.03 0.0035 0.0044 0.0044 576.50 450.00 450.05 0.0048 0.0060 0.0060 577.00 570.00 570.09 0.0061 0.0076 0.0076 577.50 520.00 520.07 0.0056 0.0069 0.0069 578.00 460.00 460.06 0.0049 0.0061 0.0049 579.00 275.00 275.02 0.0029 0.0037 0.0037 579.50 215.00 215.01 0.0023 0.0029 0.0029 580.00 170.00 170.01	572.50	240.00	240.02	0.0026	0.0032	0.0032
574.00 370.00 370.04 0.0040 0.0049 0.0049 574.50 355.00 355.03 0.0038 0.0047 0.0047 575.00 310.00 310.03 0.0033 0.0041 0.0041 575.50 285.00 285.02 0.0030 0.0038 0.0038 576.00 330.00 330.03 0.0035 0.0044 0.0044 576.50 450.00 450.05 0.0048 0.0060 0.0060 577.00 570.00 570.09 0.0061 0.0076 0.0076 577.50 520.00 520.07 0.0056 0.0069 0.0069 578.00 460.00 460.06 0.0049 0.0061 0.0061 579.50 365.00 365.04 0.0039 0.0049 0.0049 579.50 215.00 275.02 0.0029 0.0029 0.0029 580.00 170.00 170.01 0.0018 0.0023 0.0023 580.50 155.00 155.01 0.0017 0.0021 0.0021	573.00	270.00	270.02	0.0029	0.0036	0.0036
574.50 355.00 355.03 0.0038 0.0047 0.0047 575.00 310.00 310.03 0.0033 0.0041 0.0041 575.50 285.00 285.02 0.0030 0.0038 0.0038 576.00 330.00 330.03 0.0035 0.0044 0.0044 576.50 450.00 450.05 0.0048 0.0060 0.0060 577.00 570.00 570.09 0.0061 0.0076 0.0076 577.50 520.00 520.07 0.0056 0.0069 0.0069 578.00 460.00 460.06 0.0049 0.0061 0.0061 579.50 365.00 365.04 0.0039 0.0049 0.0049 579.50 215.00 275.02 0.0029 0.0037 0.0037 580.00 170.00 170.01 0.0018 0.0023 0.0023 580.50 155.00 155.01 0.0017 0.0021 0.0021	573.50	370.00	370.04	0.0040	0.0049	0.0049
575.00 310.00 310.03 0.0033 0.0041 0.0041 575.50 285.00 285.02 0.0030 0.0038 0.0038 576.00 330.00 330.03 0.0035 0.0044 0.0044 576.50 450.00 450.05 0.0048 0.0060 0.0060 577.00 570.00 570.09 0.0061 0.0076 0.0076 577.50 520.00 520.07 0.0056 0.0069 0.0069 578.00 460.00 460.06 0.0049 0.0061 0.0061 579.50 365.00 365.04 0.0039 0.0049 0.0049 579.50 275.00 275.02 0.0029 0.0037 0.0037 580.00 170.00 170.01 0.0018 0.0023 0.0023 580.50 155.00 155.01 0.0017 0.0021 0.0021	574.00	370.00	370.04	0.0040	0.0049	0.0049
575.50 285.00 285.02 0.0030 0.0038 0.0038 576.00 330.00 330.03 0.0035 0.0044 0.0044 576.50 450.00 450.05 0.0048 0.0060 0.0060 577.00 570.00 570.09 0.0061 0.0076 0.0076 577.50 520.00 520.07 0.0056 0.0069 0.0069 578.00 460.00 460.06 0.0049 0.0061 0.0061 579.50 365.00 365.04 0.0039 0.0049 0.0049 579.50 275.00 275.02 0.0029 0.0037 0.0037 579.50 215.00 215.01 0.0023 0.0029 0.0023 580.00 170.00 170.01 0.0018 0.0023 0.0023 580.50 155.00 155.01 0.0017 0.0021 0.0021	574.50	355.00	355.03	0.0038	0.0047	0.0047
576.00 330.00 330.03 0.0035 0.0044 0.0044 576.50 450.00 450.05 0.0048 0.0060 0.0060 577.00 570.00 570.09 0.0061 0.0076 0.0076 577.50 520.00 520.07 0.0056 0.0069 0.0069 578.00 460.00 460.06 0.0049 0.0061 0.0061 578.50 365.00 365.04 0.0039 0.0049 0.0049 579.00 275.00 275.02 0.0029 0.0037 0.0037 579.50 215.00 215.01 0.0023 0.0029 0.0029 580.00 170.00 170.01 0.0018 0.0023 0.0023 580.50 155.00 155.01 0.0017 0.0021 0.0021	575.00	310.00	310.03	0.0033	0.0041	0.0041
576.50 450.00 450.05 0.0048 0.0060 0.0060 577.00 570.00 570.09 0.0061 0.0076 0.0076 577.50 520.00 520.07 0.0056 0.0069 0.0069 578.00 460.00 460.06 0.0049 0.0061 0.0061 578.50 365.00 365.04 0.0039 0.0049 0.0049 579.00 275.00 275.02 0.0029 0.0037 0.0037 579.50 215.00 215.01 0.0023 0.0029 0.0029 580.00 170.00 170.01 0.0018 0.0023 0.0023 580.50 155.00 155.01 0.0017 0.0021 0.0021	575.50	285.00	285.02	0.0030	0.0038	0.0038
577.00 570.00 570.09 0.0061 0.0076 0.0076 577.50 520.00 520.07 0.0056 0.0069 0.0069 578.00 460.00 460.06 0.0049 0.0061 0.0061 578.50 365.00 365.04 0.0039 0.0049 0.0049 579.00 275.02 0.0029 0.0037 0.0037 579.50 215.00 215.01 0.0023 0.0029 580.00 170.00 170.01 0.0018 0.0023 0.0023 580.50 155.00 155.01 0.0017 0.0021 0.0021	576.00	330.00	330.03	0.0035	0.0044	0.0044
577.50 520.00 520.07 0.0056 0.0069 0.0069 578.00 460.00 460.06 0.0049 0.0061 0.0061 578.50 365.00 365.04 0.0039 0.0049 0.0049 579.00 275.02 0.0029 0.0037 0.0037 579.50 215.00 215.01 0.0023 0.0029 0.0029 580.00 170.00 170.01 0.0018 0.0023 0.0023 580.50 155.00 155.01 0.0017 0.0021 0.0021	576.50	450.00	450.05	0.0048	0.0060	0.0060
578.00 460.00 460.06 0.0049 0.0061 0.0061 578.50 365.00 365.04 0.0039 0.0049 0.0049 579.00 275.00 275.02 0.0029 0.0037 0.0037 579.50 215.00 215.01 0.0023 0.0029 0.0029 580.00 170.00 170.01 0.0018 0.0023 0.0023 580.50 155.00 155.01 0.0017 0.0021 0.0021	577.00	570.00	570.09	0.0061	0.0076	0.0076
578.50 365.00 365.04 0.0039 0.0049 0.0049 579.00 275.00 275.02 0.0029 0.0037 0.0037 579.50 215.00 215.01 0.0023 0.0029 0.0029 580.00 170.00 170.01 0.0018 0.0023 0.0023 580.50 155.00 155.01 0.0017 0.0021 0.0021	577.50	520.00	520.07	0.0056	0.0069	0.0069
579.00 275.00 275.02 0.0029 0.0037 0.0037 579.50 215.00 215.01 0.0023 0.0029 0.0029 580.00 170.00 170.01 0.0018 0.0023 0.0023 580.50 155.00 155.01 0.0017 0.0021 0.0021	578.00	460.00	460.06	0.0049	0.0061	0.0061
579.50 215.00 215.01 0.0023 0.0029 0.0029 580.00 170.00 170.01 0.0018 0.0023 0.0023 580.50 155.00 155.01 0.0017 0.0021 0.0021	578.50	365.00	365.04	0.0039	0.0049	0.0049
580.00 170.01 0.0018 0.0023 0.0023 580.50 155.00 155.01 0.0017 0.0021 0.0021	579.00	275.00	275.02	0.0029	0.0037	0.0037
580.50 155.00 155.01 0.0017 0.0021 0.0021	579.50	215.00	215.01	0.0023	0.0029	0.0029
	580.00	170.00	170.01	0.0018	0.0023	0.0023
581.00 130.00 130.00 0.0014 0.0017 0.0017	580.50	155.00	155.01	0.0017	0.0021	0.0021
	581.00	130.00	130.00	0.0014	0.0017	0.0017

Figure 23



The Assay for KVD's Exploratory Garcia 1607, "B" Sand, is shown in Figures 24 and 25, and in Table XIV.


Figure 25 illustrates the spread between the estimated ore grade values across the "B" Sand in the Garcia 1607 Well, and the 0.11 %U3O8 and 0.13 %U3O8 curves, the set cut-off values for mining.



55

KVD's Expl. Garcia 1607					
DEPTH	GAMMA-HI CPS PROBE COUNTS	GAMMA-HI CPS, CORRECTED	%U3O8 RADIOMETRIC GRADE PER UNIT	HOLE SIZE AND WATER CORR.	STEEL CASING CORRECTION
550.00	597	597.58	0.0074	0.0087	0.0087
550.50	574	573.90	0.0071	0.0084	0.0084
551.00	535	534.89	0.0066	0.0078	0.0078
551.50	421	420.66	0.0052	0.0061	0.0061
552.00	451	451.30	0.0056	0.0066	0.0066
552.50	571	571.11	0.0070	0.0083	0.0083
553.00	720	720.19	0.0089	0.0105	0.0105
553.50	811	810.75	0.0100	0.0118	0.0118
554.00	795	795.42	0.0098	0.0116	0.0116
554.50	731	731.33	0.0090	0.0106	0.0106
555.00	696	696.50	0.0086	0.0101	0.0101
555.50	762	761.98	0.0094	0.0111	0.0111
556.00	798	798.21	0.0098	0.0116	0.0116
556.50	721	721.58	0.0089	0.0105	0.0105
557.00	571	571.11	0.0070	0.0083	0.0083
557.50	529	529.32	0.0065	0.0077	0.0077
558.00	582	582.26	0.0072	0.0085	0.0085
558.50	611	611.51	0.0075	0.0089	0.0089
559.00	557	557.18	0.0069	0.0081	0.0081
559.50	565	565.54	0.0070	0.0082	0.0082
560.00	592	592.01	0.0073	0.0086	0.0086

Figure 25



The Assay for KVD's Exploratory Garcia 1607, "AA" Sand, is shown in Figures 26 and 27, and in Table XV.

Figure 27 illustrates the spread between the estimated ore grade values across the "AA" Sand in the Garcia 1607 Well, and the 0.11 %U3O8 and 0.13 %U3O8 curves, the set cut-off values for mining.

Figure 26





Table XV

VD's Garcia 1607 "AA"	Sand			772200		
DEPTH	GAMMA-HI CPS PROBE COUNTS	GAMMA-HI CPS, CORRECTED	%U3O8 RADIOMETRIC GRADE PER UNIT	HOLE SIZE AND WATER CORR.	STEEL CASING CORRECTION	
715.0	200	200.01	0.0025	0.0028	0.0028	
715.5	250	250.02	0.0031	0.0035	0.0035	
716.0 716.5	300 450	300.02 450.05	4 33 33 3 3 3 60	0.0043 0.0064	0.0043 0.0064	
717.0	580	580.08	0.0072	0.0082	0.0082	
717.5	590	590.09	0.0073	0.0084	0.0084	
718.0	550	550.08	0.0068	0.0078	0.0078	
718.5	500	500.06	0.0062	0.0071	0.0071	
719.0	500	500.06	0.0062	0.0071	0.0071	
719.5	540	540.07	0.0067	0.0077	0.0077	
720.0	610	610.09	0.0075	0.0086	0.0086	
720.5	700	700.12	0.0086	0.0099	0.0099	
721.0	880	880.19	0.0109	0.0125	0.0125	
721.5	1000	1000.25	0.0123	0.0142	0.0142	
722.0	1140	1140.32	0.0141	0.0162	0.0162	
722.5	1300	1300.42	0.0160	0.0184	0.0184	
723.0	1400	1400.49	0.0173	0.0199	0.0199	
723.5	1355	1355.46	0.0167	0.0192	0.0192	
724.0	1225	1225.38	0.0151	0.0174	0.0174	
724.5	1215	1215.37	0.0150	0.0172	0.0172	
725.0	1250	1250.39	0.0154	0.0177	0.0177	
725.5	1200	1200.36	0.0148	0.0170	0.0170	
726.0	1250	1250.39	0.0154	0.0177	0.0177	
726.5	1275	1275.41	0.0157	0.0181	0.0181	
727.0	1550	1550.60	0.0191	0.0220	0.0220	
727.5	2200	2201.21	0.0272	0.0312	0.0312	
728.0	2700	2701.82	0.0333	0.0383	0.0383	
728.5	3085	3087.38	533 (57.515)	0.0438	0.0438	
729.0	3085	3087.38	200000000	0.0438	0.0438	
729.5	2900	2902.10		0.0411	0.0411	
730.0	2640	2641.74		0.0374	0.0374	
730.5	\$700 E.S.	2391.43		0.0339	0.0339	
731.0		1900.90		0.0269	\$5.00 minutes	
731.5		1200.36		0.0170	0.0170	
732.0		800.16		0.0113	0.0113	
732.5		500.06		0.0071	0.0071	
733.0	30,00	350.03		0.0050	0.0050	
733.5	250	250.02	0.0031	0.0035	0.0035	

Figure 27



The Assay for KVD's Exploratory Garcia 1622, "B" Sand, is shown in Figures 28 and 29, and in Table XVI.

Figure 29 illustrates the proximity between the estimated ore grade values across the "B" Sand in the Garcia 1622 Well, and the 0.11 %U3O8 and 0.13 %U3O8 curves, the set cut-off values for mining.





Table XVI


(VDs Garcia 1622 "B" San	d					
DEPTH	GAMMA-HI CPS PROBE COUNTS	GAMMA-HI CPS, CORRECTED	%U3O8 RADIOMETRIC GRADE PER UNIT	HOLE SIZE AND WATER CORR. GRADE	STEEL CASING CORRECTED GRADE	
565.00	1000.00	1000.25	0.0129	0.0148	0.0148	
565.50	1600.00	1600.64	0.0206	0.0237	0.0237	
566.00	2400.00	2401.44	0.0309	0.0355	0.0355	
566.50	3400.00	3402.89	0.0438	0.0503	0.0503	
567.00	3700.00	3703.43	0.0477	0.0548	0.0548	
567.50	4100.00	4104.21	0.0529	0.0607	0.0607	
568.00	3800.00	3803.61	0.0490	0.0563	0.0563	
568.50	3100.00	3102.40	0.0400	0.0459	0.0459	
569.00	2300.00	2301.32	0.0296	0.0340	0.0340	
569.50	1500.00	1500.56	0.0193	0.0222	0.0222	
570.00	1000.00	1000.25	0.0129	0.0148	0.0148	
580.00	800.00	800.16	0.0103	0.0118	0.0118	
580.50	1000.00	1000.25	0.0129	0.0148	0.0148	
585.50	10600.00	10628.16	0.1369	0.1572	0.1572	
586.00	10000.00	10025.06	0.1291	0.1483	0.1483	
586.50	8500.00	8518.10	0.1097	0.1260	0.1260	
587.00	7200.00	7212.98	0.0929	0.1067	0.1067	
587.50	5400.00	5407.30	0.0696	0.0800	0.0800	
588.00	4100.00	4104.21	0.0529	0.0607	0.0607	
588.50	3300.00	3302.72	0.0425	0.0489	0.0489	
589.00	2900.00	2902.10	0.0374	0.0429	0.0429	
589.50	2400.00	2401.44	0.0309	0.0355	0.0355	
590.00	1900.00	1900.90	0.0245	0.0281	0.0281	
590.50	1500.00	1500.56	0.0193	0.0222	0.0222	
591.00	1100.00	1100.30	0.0142	0.0163	0.0163	

Figure 29



The Assay for KVD's Exploratory Garcia 1619, "B" Sand, is shown in Figures 30 and 31, and in Table XVII.

Figure 26 illustrates the spread between the estimated ore grade values across the "B" Sand in the Garcia 1619 Well, and the 0.11 %U3O8 and 0.13 %U3O8 curves, the set cut-off values for mining.




KVD's Exploratory Garcia 1619 – "B" Sand – GR Recorded & Digitized Curves Comparison

Table XVII

VD's Garcia 1619 "B" Sa	ind					
DEPTH	GAMMA-HI CPS PROBE COUNTS	GAMMA-HI CPS, CORRECTED	%U3O8 RADIOMETRIC GRADE PER UNIT	HOLE SIZE AND WATER CORR.	STEEL CASING CORRECTION	
567.00	448	448.33	0.0055	0.0065	0.0065	
567.50	579	578.63	0.0071	0.0083	0.0083	
568.00	762	762.60	0.0094	0.0110	0.0110	
568.50	1054	1053.92	0.0130	0.0152	0.0152	
569.00	1253	1253.27	0.0155	0.0180	0.0180	
569.50	1402	1402.79	0.0173	0.0202	0.0202	
570.00	1368	1368.28	0.0169	0.0197	0.0197	
570.50	1272	1272.44	0.0157	0.0183	0.0183	
571.00	1268	1268.60	0.0157	0.0183	0.0183	
571.50	1410	1410.46	0.0174	0.0203	0.0203	
572.00	1590	1590.67	0.0196	0.0229	0.0229	
572.50	1490	1490.98	0.0184	0.0215	0.0215	
573.00	1100	1099.92	0.0136	0.0158	0.0158	
573.50	701	701.27	0.0087	0.0101	0.0101	
574.00	517	517.31	0.0064	0.0074	0.0074	

Figure 31



The Assay for KVD's Exploratory Garcia 1619, "AA" Sand, is shown in Figures 32 and 33, and in Table XVIII.

Figure 33 illustrates the spread between the estimated ore grade values across the "AA" Sand in the Garcia 1619 Well, and the 0.11 %U3O8 and 0.13 %U3O8 curves, the set cut-off values for mining.




Table XVIII

s Garcia 1619 "AA" Sa	ind				
DEPTH	GAMMA-HI CPS PROBE COUNTS	GAMMA-HI CPS, CORRECTED	%U3O8 RADIOMETRIC GRADE PER UNIT	HOLE SIZE AND WATER CORR.	STEEL CASING CORRECTION
720.0	117	117.19	0.0014	0.0017	0.0017
720.5	135	135.16	0.0017	0.0019	0.0019
721.0	134	134.38	0.0017	0.0019	0.0019
721.5	134	133.60	0.0016	0.0019	0.0019
722.0	148	148.44	0.0018	0.0021	0.0021
722.5	227	226.58	0.0028	0.0033	0.0033
723.0	278	278.14	0.0034	0.0040	0.0040
723.5	291	291.43	0.0036	0.0042	0.0042
724.0	348	347.69	0.0043	0.0050	0.0050
724.5	422	421.92	0.0052	0.0061	0.0061
725.0	448	448.49	0.0055	0.0065	0.0065
725.5	470	470.37	0.0058	0.0068	0.0068
726.0	493	493.03	0.0061	0.0071	0.0071
726.5	490	489.90	0.0060	0.0071	0.0071
727.0	478	478.18	0.0059	0.0069	0.0069
727.5	421	421.14	0.0052	0.0061	0.0061
728.0	361	360.97	0.0045	0.0052	0.0052
728.5	327	327.37	0.0040	0.0047	0.0047
729.0	336	335.97	0.0041	0.0048	0.0048
729.5	323	322.68	0.0040	0.0046	0.0046
730.0	277	276.58	0.0034	0.0040	0.0040

Figure 33

